



ŠKODA
SIMPLY CLEVER

ŠKODA KODIAQ

Petrol engines

Technical specifications	1.4 TSI/110 kW ACT 4x4	1.4 TSI/110 kW 4x4 (A)	2.0 TSI/132 kW 4x4 (A)
Engine			
Engine type	turbocharged petrol engine, in-line, liquid cooling system, DOHC, transverse in front		
Cylinders	4		
Displacement [cm ³]	1395		1984
Bore × Stroke [mm × mm]	74.5 × 80.0		82.5 × 92.8
Max. engine performance/revs [kW at rpm]	110/5000–6000		132/3900–6000
Max. torque/revs [Nm at rpm]	250/1500–3500		320/1400–3940
Compression ratio	10.0 : 1		11.65 : 1
Emission limit	EU 6		
Fuel injection system	electronically controlled direct injection		electronically controlled combined (direct and port) injection
Ignition	control unit controlled electronic ignition system		
Lubrication	force-feed lubrication with through-flow oil filter		
Fuel quality	unleaded petrol min. RON 95		
Transmission			
Wheel drive	four-wheel drive with automatic torque distribution		
Clutch	hydraulic single dry clutch disc with membrane spring, asbestos free	two coaxial dry multiple-disk clutch, electro-hydraulically operated	
Transmission	manual 6-speed fully synchronized	automatic 6-speed, DSG, with Tiptronic manual gear changing	automatic 7-speed, DSG, with Tiptronic manual gear changing
Transmission ratio	I-3.769 II-2.087 III-1.469 IV-1.088 V-1.108 VI-0.912 R-4.549	I-3.462 II-2.050 III-1.300 IV-0.902 V-0.914 VI-0.756 R-3.987	I-3.562 II-2.526 III-1.679 IV-1.022 V-0.788 VI-0.761 VII-0.635 R-2.788
Axle ratio	I-4.562 II-3.476	I-4.800 II-3.600	I-4.733 II-3.944



ŠKODA
SIMPLY CLEVER

ŠKODA KODIAQ

Petrol engines

Technical specifications	1.4 TSI/110 kW ACT 4x4	1.4 TSI/110 kW 4x4 (A)	2.0 TSI/132 kW 4x4 (A)
Chassis			
Front axle	MacPherson suspension with lower triangular links and torsion stabiliser		
Rear axle	multi-element axle, with one longitudinal and three transverse links, with torsion stabiliser		
Springs	telescopic shock absorbers with coil springs, in the rear outside the springs		
Braking system	hydraulic diagonal dual-circuit braking system, vacuum servo assisted		
Brake – front	disc brakes with inner cooling, with single/piston floating caliper		
Brake – rear	disc brakes		
Parking brake	electromechanical, on rear wheels		
Steering system	direct rack and pinion steering with electro mechanic power steering		
Wheels	7J x 17"		
Tyres	215/65 R17		
Body			
Body	5 door, two compartment, 5 seater {7 seater}		
Drag coefficient c_w	0.332 {0.341}	0.332 {0.341}	0.330 {0.336}
Outside dimensions			
Length [mm]	4697		
Width [mm]	1882		
Height (at kerb weight) [mm]	1655		
Wheel base [mm]	2791		
Clearance (at kerb weight) [mm]	187 {189}		
Track front [mm]	1586		
Track rear [mm]	1576		



ŠKODA
SIMPLY CLEVER

ŠKODA KODIAQ

Petrol engines

Technical specifications		1.4 TSI/110 kW ACT 4x4	1.4 TSI/110 kW 4x4 (A)	2.0 TSI/132 kW 4x4 (A)
Inside dimensions				
Width of front seats	[mm]		1527	
Width of rear seats (2 nd /3 rd row)	[mm]		1510/- {1511/1270}	
Headroom in front seats	[mm]		1020	
Headroom in rear seats (2 nd /3 rd row)	[mm]		1014/- {1015/905}	
Storage capacity (behind 3 rd row of seats up to headrests, boot cover is stored under the boot floor)	[l]		{270***}	
Storage capacity up to the rear shelf (with 3 rd row of seats folded down, depending on position of backrest, and depending on the position of adjustable 2 nd row of seats)	[l]		650-835*** {560-765***}	
Storage capacity with rear seats folded down, up to the roof	[l]		2065 {2005}	
Weights				
Kerb weight – incl. driver**	[kg]	1615 {1658}	1630 {1673}	1695 {1738}
Payload – incl. driver**	[kg]	675 {762}	675 {761}	675 {762}
Total weight	[kg]	2215 {2335}	2230 {2350}	2295 {2413}
Max. roof load	[kg]		75	
Max. trailer load w/o brakes	[kg]		750	
Max. trailer load with brakes – 12%	[kg]	2000	2000	2200 {2000}
Max. trailer load with brakes – 8%	[kg]	2000	2000	2200 {2000}
Max. nose weight	[kg]		100 {80}	



ŠKODA
SIMPLY CLEVER

ŠKODA KODIAQ

Petrol engines

Technical specifications	1.4 TSI/110 kW ACT 4×4	1.4 TSI/110 kW 4×4 (A)	2.0 TSI/132 kW 4×4 (A)
Liquids			
Tank capacity [l]	60		
Performance/consumption			
Maximum speed [km/h]	197 {196}	194 {192}	207 {205}
Acceleration 0–100 km/h [s]	9.8 {9.9}	9.9 {10.1}	8.0 {8.2}
Fuel consumption (1999/100/EC)			
Consumption – urban [l/100 km]	8.2	8.4	9.0
Consumption – extra-urban [l/100 km]	5.9	6.2	6.3
Consumption – combined [l/100 km]	6.8	7.0	7.3
CO ₂ emissions [g/km]	153 {154}	161	168
Turning circle diameter [m]	11.6		

The technical data is valid for the basic version.

** Figures apply to basic version, weight of driver 75 kg.

*** The capacity depends on the position of the backrests and rear seats.

{ } Applies to 7-seater.



ŠKODA
SIMPLY CLEVER

ŠKODA KODIAQ

Diesel engines

Technical specifications	2.0 TDI/110 kW 4x4	2.0 TDI/110 kW 4x4 (A)	2.0 TDI/140 kW 4x4 (A)
Engine			
Engine type	turbocharged diesel engine, turbocharger with self-aligning blades, in-line, liquid cooling system, DOHC, transverse in front		
Cylinders	4		
Displacement [cm ³]	1968		
Bore × Stroke [mm × mm]	81.0 × 95.5		
Max. engine performance/revs [kW at rpm]	110/3500–4000		140/3500–4000
Max. torque/revs [Nm at rpm]	340/1750–3000		400/1750–3250
Compression ratio	16.2 : 1		15.5 : 1
Emission limit	EU 6		
Fuel injection system	electronically controlled high-pressure direct injection – common-rail system		
Lubrication	force-feed lubrication with through-flow oil filter		
Fuel quality	diesel		
Transmission			
Wheel drive	four-wheel drive with automatic torque distribution		
Clutch	hydraulic single dry clutch disc with membrane spring, asbestos free	two coaxial wet multiple-disk clutch, electro-hydraulically operated	
Transmission	manual 6-speed fully synchronized	automatic 7-speed, DSG, with Tiptronic manual gear changing	
Transmission ratio	I-3.769 II-2.087 III-1.324 IV-0.977 V-0.975 VI-0.814 R-4.549	I-3.562 II-2.526 III-1.586 IV-0.938 V-0.722 VI-0.688 VII-0.574 R-2.788	I-3.562 II-2.526 III-1.586 IV-0.938 V-0.722 VI-0.688 VII-0.574 R-2.788
Axle ratio	I-3.944 II-3.087	I-4.733 II-3.944	I-4.733 II-3.944
Chassis			
Front axle	MacPherson suspension with lower triangular links and torsion stabiliser		
Rear axle	multi-element axle, with one longitudinal and three transverse links, with torsion stabiliser		
Springs	telescopic shock absorbers with coil springs, in the rear outside the springs		
Braking system	hydraulic diagonal dual-circuit braking system, vacuum servo assisted		
Brake – front	disc brakes with inner cooling, with single/piston floating caliper		
Brake – rear	disc brakes		
Parking brake	electromechanical, on rear wheels		
Steering system	direct rack and pinion steering with electro mechanic power steering		
Wheels	7J × 17"		
Tyres	215/65 R17		



ŠKODA
SIMPLY CLEVER

ŠKODA KODIAQ

Diesel engines

Technical specifications		2.0 TDI/110 kW 4×4	2.0 TDI/110 kW 4×4 (A)	2.0 TDI/140 kW 4×4 (A)
Body				
Body		5 door, two compartment, 5 seater {7 seater}		
Drag coefficient c_w		0.331 {0.341}		0.334 {0.338}
Outside dimensions				
Length	[mm]	4697		
Width	[mm]	1882		
Height (at kerb weight)	[mm]	1655		
Wheel base	[mm]	2791		
Clearance (at kerb weight)	[mm]	187 {189}		
Track front	[mm]	1586		
Track rear	[mm]	1576		
Inside dimensions				
Width of front seats	[mm]	1527		
Width of rear seats (2 nd /3 rd row)	[mm]	1510/- {1511/1270}		
Headroom in front seats	[mm]	1020		
Headroom in rear seats (2 nd /3 rd row)	[mm]	1014/- {1015/905}		
Storage capacity (behind 3 rd row of seats up to headrests, boot cover is stored under the boot floor)	[l]	{270***}		
Storage capacity up to the rear shelf (with 3 rd row of seats folded down, depending on position of backrest, and depending on the position of adjustable 2 nd row of seats)	[l]	650-835*** {560-765***}		
Storage capacity with rear seats folded down, up to the roof	[l]	2065 {2005}		



ŠKODA
SIMPLY CLEVER

ŠKODA KODIAQ

Diesel engines

Technical specifications		2.0 TDI/110 kW 4x4	2.0 TDI/110 kW 4x4 (A)	2.0 TDI/140 kW 4x4 (A)
Weights				
Kerb weight – incl. driver**	[kg]	1705 {1748}	1740 {1783}	1752 {1795}
Payload – incl. driver**	[kg]	675 {710}	675 {768}	675 {767}
Total weight	[kg]	2305 {2383}	2340 {2460}	2352 {2472}
Max. roof load	[kg]	75		
Max. trailer load w/o brakes	[kg]	750 {-}	750	
Max. trailer load with brakes – 12%	[kg]	2000 {-}	2500 {2000}	
Max. trailer load with brakes – 8%	[kg]	2000 {-}	2500 {2000}	
Max. nose weight	[kg]	100 {-}	100 {80}	
Liquids				
Tank capacity	[l]	60		
Performance/consumption				
Maximum speed	[km/h]	197 {195}	194 {192}	210 {209}
Acceleration 0–100 km/h	[s]	9.7 {9.9}	9.9 {10.1}	8.6 {8.8}
Fuel consumption (1999/100/EC)				
Consumption – urban	[l/100 km]	6.3 {6.4}	6.7	6.6
Consumption – extra-urban	[l/100 km]	4.7 {4.8}	5.1	5.3
Consumption – combined	[l/100 km]	5.3 {5.4}	5.6	5.7
CO ₂ emissions	[g/km]	139 {142}	147	150 {151}
Turning circle diameter	[m]	11.6		

The technical data is valid for the basic version.

** Figures apply to basic version, weight of driver 75 kg.

*** The capacity depends on the position of the backrests and rear seats.

{ } Applies to 7-seater.



ŠKODA
SIMPLY CLEVER

ŠKODA KODIAQ SPORTLINE

Petrol engines

Technical specifications	1.4 TSI/110 kW ACT 4x4	1.4 TSI/110 kW 4x4 (A)	2.0 TSI/132 kW 4x4 (A)
Engine			
Engine type	turbocharged petrol engine, in-line, liquid cooling system, DOHC, transverse in front		
Cylinders	4		
Displacement [cm ³]	1395		1984
Bore × Stroke [mm × mm]	74.5 × 80.0		82.5 × 92.8
Max. engine performance/revs [kW at rpm]	110/5000–6000		132/3900–6000
Max. torque/revs [Nm at rpm]	250/1500–3500		320/1400–3940
Compression ratio	10.0 : 1		11.65 : 1
Emission limit	EU 6		
Fuel injection system	electronically controlled direct injection		electronically controlled combined (direct and port) injection
Ignition	control unit controlled electronic ignition system		
Lubrication	force-feed lubrication with through-flow oil filter		
Fuel quality	unleaded petrol min. RON 95		
Transmission			
Wheel drive	four-wheel drive with automatic torque distribution		
Clutch	hydraulic single dry clutch disc with membrane spring, asbestos free	two coaxial dry multiple-disk clutch, electro-hydraulically operated	
Transmission	manual 6-speed fully synchronized	automatic 6-speed, DSG, with Tiptronic manual gear changing	automatic 7-speed, DSG, with Tiptronic manual gear changing
Transmission ratio	I-3.769 II-2.087 III-1.469 IV-1.088 V-1.108 VI-0.912 R-4.549	I-3.462 II-2.050 III-1.300 IV-0.902 V-0.914 VI-0.756 R-3.987	I-3.562 II-2.526 III-1.679 IV-1.022 V-0.788 VI-0.761 VII-0.635 R-2.788
Axle ratio	I-4.562 II-3.476	I-4.800 II-3.600	I-4.733 II-3.944



ŠKODA
SIMPLY CLEVER

ŠKODA KODIAQ SPORTLINE

Petrol engines

Technical specifications	1.4 TSI/110 kW ACT 4×4	1.4 TSI/110 kW 4×4 (A)	2.0 TSI/132 kW 4×4 (A)
Chassis			
Front axle	MacPherson suspension with lower triangular links and torsion stabiliser		
Rear axle	multi-element axle, with one longitudinal and three transverse links, with torsion stabiliser		
Springs	telescopic shock absorbers with coil springs, in the rear outside the springs		
Braking system	hydraulic diagonal dual-circuit braking system, vacuum servo assisted		
Brake – front	disc brakes with inner cooling, with single/piston floating caliper		
Brake – rear	disc brakes		
Parking brake	electromechanical, on rear wheels		
Steering system	direct rack and pinion steering with electro mechanic power steering		
Wheels	7J × 19"		
Tyres	235/50 R19		
Body			
Body	5 door, two compartment, 5 seater {7 seater}		
Drag coefficient c_w	0.332 {0.341}	0.332 {0.341}	0.330 {0.336}
Outside dimensions			
Length [mm]	4700		
Width [mm]	1882		
Height (at kerb weight) [mm]	1676		
Wheel base [mm]	2791		
Clearance (at kerb weight) [mm]	187 {189}		
Track front [mm]	1586		
Track rear [mm]	1576		



ŠKODA
SIMPLY CLEVER

ŠKODA KODIAQ SPORTLINE

Petrol engines

Technical specifications	1.4 TSI/110 kW ACT 4x4	1.4 TSI/110 kW 4x4 (A)	2.0 TSI/132 kW 4x4 (A)
Inside dimensions			
Width of front seats [mm]		1527	
Width of rear seats (2 nd /3 rd row) [mm]		1510/- {1511/1270}	
Headroom in front seats [mm]		1020	
Headroom in rear seats (2 nd /3 rd row) [mm]		1014/- {1015/905}	
Storage capacity (behind 3 rd row of seats up to headrests, boot cover is stored under the boot floor) [l]		{270***}	
Storage capacity up to the rear shelf (with 3 rd row of seats folded down, depending on position of backrest, and depending on the position of adjustable 2 nd row of seats) [l]		650-835*** {560-765***}	
Storage capacity with rear seats folded down, up to the roof [l]		2065 {2005}	
Weights			
Kerb weight – incl. driver** [kg]	1615 {1658}	1630 {1673}	1695 {1738}
Payload – incl. driver** [kg]	675 {762}	675 {761}	675 {762}
Total weight [kg]	2215 {2335}	2230 {2350}	2295 {2413}
Max. roof load [kg]		75	
Max. trailer load w/o brakes [kg]		750	
Max. trailer load with brakes – 12% [kg]	2000	2000	2200 {2000}
Max. trailer load with brakes – 8% [kg]	2000	2000	2200 {2000}
Max. nose weight [kg]	100 {80}		100 {80}



ŠKODA
SIMPLY CLEVER

ŠKODA KODIAQ SPORTLINE

Petrol engines

Technical specifications	1.4 TSI/110 kW ACT 4×4	1.4 TSI/110 kW 4×4 (A)	2.0 TSI/132 kW 4×4 (A)
Liquids			
Tank capacity [l]	60	60	60
Performance/consumption			
Maximum speed [km/h]	197 {196}	194 {192}	207 {205}
Acceleration 0–100 km/h [s]	9.8 {9.9}	9.9 {10.1}	8.0 {8.2}
Fuel consumption (1999/100/EC)			
Consumption – urban [l/100 km]	8.2	8.4	9.0
Consumption – extra-urban [l/100 km]	5.9	6.2	6.3
Consumption – combined [l/100 km]	6.8	7.0	7.3
CO ₂ emissions [g/km]	153 {154}	161	168
Turning circle diameter [m]		11.6	

The technical data is valid for the basic version.

** Figures apply to basic version, weight of driver 75 kg.

*** The capacity depends on the position of the backrests and rear seats.

{ } Applies to 7-seater.



ŠKODA
SIMPLY CLEVER

ŠKODA KODIAQ SPORTLINE

Diesel engines

Technical specifications	2.0 TDI/110 kW 4x4	2.0 TDI/110 kW 4x4 (A)	2.0 TDI/140 kW 4x4 (A)
Engine			
Engine type	turbocharged diesel engine, turbocharger with self-aligning blades, in-line, liquid cooling system, DOHC, transverse in front		
Cylinders	4		
Displacement [cm ³]	1968		
Bore × Stroke [mm × mm]	81.0 × 95.5		
Max. engine performance/revs [kW at rpm]	110/3500–4000		140/3500–4000
Max. torque/revs [Nm at rpm]	340/1750–3000		400/1750–3250
Compression ratio	16.2 : 1		15.5 : 1
Emission limit	EU 6		
Fuel injection system	electronically controlled high-pressure direct injection – common-rail system		
Lubrication	force-feed lubrication with through-flow oil filter		
Fuel quality	diesel		
Transmission			
Wheel drive	four-wheel drive with automatic torque distribution		
Clutch	hydraulic single dry clutch disc with membrane spring, asbestos free	two coaxial wet multiple-disk clutch, electro-hydraulically operated	
Transmission	manual 6-speed fully synchronized	automatic 7-speed, DSG, with Tiptronic manual gear changing	
Transmission ratio	I-3.769 II-2.087 III-1.324 IV-0.977 V-0.975 VI-0.814 R-4.549	I-3.562 II-2.526 III-1.586 IV-0.938 V-0.722 VI-0.688 VII-0.574 R-2.788	I-3.562 II-2.526 III-1.586 IV-0.938 V-0.722 VI-0.688 VII-0.574 R-2.788
Axle ratio	I-3.944 II-3.087	I-4.733 II-3.944	I-4.733 II-3.944
Chassis			
Front axle	MacPherson suspension with lower triangular links and torsion stabiliser		
Rear axle	multi-element axle, with one longitudinal and three transverse links, with torsion stabiliser		
Springs	telescopic shock absorbers with coil springs, in the rear outside the springs		
Braking system	hydraulic diagonal dual-circuit braking system, vacuum servo assisted		
Brake – front	disc brakes with inner cooling, with single/piston floating caliper		
Brake – rear	disc brakes		
Parking brake	electromechanical, on rear wheels		
Steering system	direct rack and pinion steering with electro mechanic power steering		
Wheels	7J × 19"		
Tyres	235/50 R19		



ŠKODA
SIMPLY CLEVER

ŠKODA KODIAQ SPORTLINE

Diesel engines

Technical specifications		2.0 TDI/110 kW 4x4	2.0 TDI/110 kW 4x4 (A)	2.0 TDI/140 kW 4x4 (A)
Body				
Body		5 door, two compartment, 5 seater {7 seater}		
Drag coefficient c_w		0.331 {0.341}		0.334 {0.338}
Outside dimensions				
Length	[mm]	4700		
Width	[mm]	1882		
Height (at kerb weight)	[mm]	1676		
Wheel base	[mm]	2791		
Clearance (at kerb weight)	[mm]	187 {189}		
Track front	[mm]	1586		
Track rear	[mm]	1576		
Inside dimensions				
Width of front seats	[mm]	1527		
Width of rear seats (2 nd /3 rd row)	[mm]	1510/- {1511/1270}		
Headroom in front seats	[mm]	1020		
Headroom in rear seats (2 nd /3 rd row)	[mm]	1014/- {1015/905}		
Storage capacity (behind 3 rd row of seats up to headrests, boot cover is stored under the boot floor)	[l]	{270***}		
Storage capacity up to the rear shelf (with 3 rd row of seats folded down, depending on position of backrest, and depending on the position of adjustable 2 nd row of seats)	[l]	650-835*** {560-765***}		
Storage capacity with rear seats folded down, up to the roof	[l]	2065 {2005}		



ŠKODA
SIMPLY CLEVER

ŠKODA KODIAQ SPORTLINE

Diesel engines

Technical specifications		2.0 TDI/110 kW 4x4	2.0 TDI/110 kW 4x4 (A)	2.0 TDI/140 kW 4x4 (A)
Weights				
Kerb weight – incl. driver**	[kg]	1705 {1748}	1740 {1783}	1752 {1795}
Payload – incl. driver**	[kg]	675 {710}	675 {768}	675 {767}
Total weight	[kg]	2305 {2383}	2340 {2460}	2352 {2472}
Max. roof load	[kg]	75		
Max. trailer load w/o brakes	[kg]	750 {-}	750	
Max. trailer load with brakes – 12%	[kg]	2000 {-}	2500 {2000}	
Max. trailer load with brakes – 8%	[kg]	2000 {-}	2500 {2000}	
Max. nose weight	[kg]	100 {-}	100 {80}	
Liquids				
Tank capacity	[l]	60		
Performance/consumption				
Maximum speed	[km/h]	197 {195}	194 {192}	210 {209}
Acceleration 0–100 km/h	[s]	9.7 {9.9}	9.9 {10.1}	8.6 {8.8}
Fuel consumption (1999/100/EC)				
Consumption – urban	[l/100 km]	6.3 {6.4}	6.7	6.6
Consumption – extra-urban	[l/100 km]	4.7 {4.8}	5.1	5.3
Consumption – combined	[l/100 km]	5.3 {5.4}	5.6	5.7
CO ₂ emissions	[g/km]	139 {142}	147	150 {151}
Turning circle diameter	[m]	11.6		

The technical data is valid for the basic version.

** Figures apply to basic version, weight of driver 75 kg.

*** The capacity depends on the position of the backrests and rear seats.

{ } Applies to 7-seater.



ŠKODA
SIMPLY CLEVER

ŠKODA KODIAQ SCOUT

Petrol engines

Technical specifications	1.4 TSI/110 kW ACT 4×4	1.4 TSI/110 kW 4×4 (A)	2.0 TSI/132 kW 4×4 (A)
Engine			
Engine type	turbocharged petrol engine, in-line, liquid cooling system, DOHC, transverse in front		
Cylinders	4		
Displacement [cm ³]	1395		1984
Bore × Stroke [mm × mm]	74.5 × 80.0		82.5 × 92.8
Max. engine performance/revs [kW at rpm]	110/5000–6000		132/3900–6000
Max. torque/revs [Nm at rpm]	250/1500–3500		320/1400–3940
Compression ratio	10.0 : 1		11.65 : 1
Emission limit	EU 6		
Fuel injection system	electronically controlled direct injection		electronically controlled combined (direct and port) injection
Ignition	control unit controlled electronic ignition system		
Lubrication	force-feed lubrication with through-flow oil filter		
Fuel quality	unleaded petrol min. RON 95		
Transmission			
Wheel drive	four-wheel drive with automatic torque distribution		
Clutch	hydraulic single dry clutch disc with membrane spring, asbestos free	two coaxial dry multiple-disk clutch, electro-hydraulically operated	
Transmission	manual 6-speed fully synchronized	automatic 6-speed, DSG, with Tiptronic manual gear changing	automatic 7-speed, DSG, with Tiptronic manual gear changing
Transmission ratio	I-3.769 II-2.087 III-1.469 IV-1.088 V-1.108 VI-0.912 R-4.549	I-3.462 II-2.050 III-1.300 IV-0.902 V-0.914 VI-0.756 R-3.987	I-3.562 II-2.526 III-1.679 IV-1.022 V-0.788 VI-0.761 VII-0.635 R-2.788
Axle ratio	I-4.562 II-3.476	I-4.800 II-3.600	I-4.733 II-3.944



ŠKODA
SIMPLY CLEVER

ŠKODA KODIAQ SCOUT

Petrol engines

Technical specifications	1.4 TSI/110 kW ACT 4×4	1.4 TSI/110 kW 4×4 (A)	2.0 TSI/132 kW 4×4 (A)
Chassis			
Front axle	MacPherson suspension with lower triangular links and torsion stabiliser		
Rear axle	multi-element axle, with one longitudinal and three transverse links, with torsion stabiliser		
Springs	telescopic shock absorbers with coil springs, in the rear outside the springs		
Braking system	hydraulic diagonal dual-circuit braking system, vacuum servo assisted		
Brake – front	disc brakes with inner cooling, with single/piston floating caliper		
Brake – rear	disc brakes		
Parking brake	electromechanical, on rear wheels		
Steering system	direct rack and pinion steering with electro mechanic power steering		
Wheels	7J × 19"		
Tyres	235/50 R19		
Body			
Body	5 door, two compartment, 5 seater {7 seater}		
Drag coefficient c_w	0.332 {0.341}	0.332 {0.341}	0.330 {0.336}
Outside dimensions			
Length [mm]	4706		
Width [mm]	1882		
Height (at kerb weight) [mm]	1676		
Wheel base [mm]	2791		
Clearance (at kerb weight) [mm]	187{189}		
Track front [mm]	1586		
Track rear [mm]	1576		



ŠKODA
SIMPLY CLEVER

ŠKODA KODIAQ SCOUT

Petrol engines

Technical specifications	1.4 TSI/110 kW ACT 4x4	1.4 TSI/110 kW 4x4 (A)	2.0 TSI/132 kW 4x4 (A)
Inside dimensions			
Width of front seats [mm]		1527	
Width of rear seats (2 nd /3 rd row) [mm]		1510/- {1511/1270}	
Headroom in front seats [mm]		1020	
Headroom in rear seats (2 nd /3 rd row) [mm]		1014/- {1015/905}	
Storage capacity (behind 3 rd row of seats up to headrests, boot cover is stored under the boot floor) [l]		{270***}	
Storage capacity up to the rear shelf (with 3 rd row of seats folded down, depending on position of backrest, and depending on the position of adjustable 2 nd row of seats) [l]		650-835*** {560-765***}	
Storage capacity with rear seats folded down, up to the roof [l]		2065 {2005}	
Weights			
Kerb weight – incl. driver** [kg]	1615 {1658}	1630 {1673}	1695 {1738}
Payload – incl. driver** [kg]	675 {762}	675 {761}	675 {762}
Total weight [kg]	2215 {2335}	2230 {2350}	2295 {2413}
Max. roof load [kg]		75	
Max. trailer load w/o brakes [kg]		750	
Max. trailer load with brakes – 12% [kg]	2000	2000	2200 {2000}
Max. trailer load with brakes – 8% [kg]	2000	2000	2200 {2000}
Max. nose weight [kg]	100 {80}		100 {80}
Liquids			
Tank capacity [l]		60	



ŠKODA
SIMPLY CLEVER

ŠKODA KODIAQ SCOUT

Petrol engines

Technical specifications		1.4 TSI/110 kW ACT 4×4	1.4 TSI/110 kW 4×4 (A)	2.0 TSI/132 kW 4×4 (A)
Performance/consumption				
Maximum speed	[km/h]	197 {196}	194 {192}	207 {205}
Acceleration 0–100 km/h	[s]	9.8 {9.9}	9.9 {10.1}	8.0 {8.2}
Fuel consumption (1999/100/EC)				
Consumption – urban	[l/100 km]	8.2	8.4	9.0
Consumption – extra-urban	[l/100 km]	5.9	6.2	6.3
Consumption – combined	[l/100 km]	6.8	7.0	7.3
CO ₂ emissions	[g/km]	153 {154}	161	168
Turning circle diameter	[m]		11.6	

The technical data is valid for the basic version.

** Figures apply to basic version, weight of driver 75 kg.

*** The capacity depends on the position of the backrests and rear seats.

{ } Applies to 7-seater.



ŠKODA
SIMPLY CLEVER

ŠKODA KODIAQ SCOUT

Diesel engines

Technical specifications	2.0 TDI/110 kW 4x4	2.0 TDI/110 kW 4x4 (A)	2.0 TDI/140 kW 4x4 (A)
Engine			
Engine type	turbocharged diesel engine, turbocharger with self-aligning blades, in-line, liquid cooling system, DOHC, transverse in front		
Cylinders	4		
Displacement [cm ³]	1968		
Bore × Stroke [mm × mm]	81.0 × 95.5		
Max. engine performance/revs [kW at rpm]	110/3500–4000		140/3500–4000
Max. torque/revs [Nm at rpm]	340/1750–3000		400/1750–3250
Compression ratio	16.2 : 1		15.5 : 1
Emission limit	EU 6		
Fuel injection system	electronically controlled high-pressure direct injection – common-rail system		
Lubrication	force-feed lubrication with through-flow oil filter		
Fuel quality	diesel		
Transmission			
Wheel drive	four-wheel drive with automatic torque distribution		
Clutch	hydraulic single dry clutch disc with membrane spring, asbestos free	two coaxial wet multiple-disk clutch, electro-hydraulically operated	
Transmission	manual 6-speed fully synchronized	automatic 7-speed, DSG, with Tiptronic manual gear changing	
Transmission ratio	I-3.769 II-2.087 III-1.324 IV-0.977 V-0.975 VI-0.814 R-4.549	I-3.562 II-2.526 III-1.586 IV-0.938 V-0.722 VI-0.688 VII-0.574 R-2.788	I-3.562 II-2.526 III-1.586 IV-0.938 V-0.722 VI-0.688 VII-0.574 R-2.788
Axle ratio	I-3.944 II-3.087	I-4.733 II-3.944	I-4.733 II-3.944
Chassis			
Front axle	MacPherson suspension with lower triangular links and torsion stabiliser		
Rear axle	multi-element axle, with one longitudinal and three transverse links, with torsion stabiliser		
Springs	telescopic shock absorbers with coil springs, in the rear outside the springs		
Braking system	hydraulic diagonal dual-circuit braking system, vacuum servo assisted		
Brake – front	disc brakes with inner cooling, with single/piston floating caliper		
Brake – rear	disc brakes		
Parking brake	electromechanical, on rear wheels		
Steering system	direct rack and pinion steering with electro mechanic power steering		
Wheels	7J × 19"		
Tyres	235/50 R19		



ŠKODA
SIMPLY CLEVER

ŠKODA KODIAQ SCOUT

Diesel engines

Technical specifications		2.0 TDI/110 kW 4x4	2.0 TDI/110 kW 4x4 (A)	2.0 TDI/140 kW 4x4 (A)
Body				
Body		5 door, two compartment, 5 seater {7 seater}		
Drag coefficient c_w		0.331 {0.341}		0.334 {0.338}
Outside dimensions				
Length	[mm]	4706		
Width	[mm]	1882		
Height (at kerb weight)	[mm]	1676		
Wheel base	[mm]	2791		
Clearance (at kerb weight)	[mm]	187 {189}		
Track front	[mm]	1586		
Track rear	[mm]	1576		
Inside dimensions				
Width of front seats	[mm]	1527		
Width of rear seats (2 nd /3 rd row)	[mm]	1510/- {1511/1270}		
Headroom in front seats	[mm]	1020		
Headroom in rear seats (2 nd /3 rd row)	[mm]	1014/- {1015/905}		
Storage capacity (behind 3 rd row of seats up to headrests, boot cover is stored under the boot floor)	[l]	{270***}		
Storage capacity up to the rear shelf (with 3 rd row of seats folded down, depending on position of backrest, and depending on the position of adjustable 2 nd row of seats)	[l]	650-835*** {560-765***}		
Storage capacity with rear seats folded down, up to the roof	[l]	2065 {2005}		



ŠKODA
SIMPLY CLEVER

ŠKODA KODIAQ SCOUT

Diesel engines

Technical specifications		2.0 TDI/110 kW 4×4	2.0 TDI/110 kW 4×4 (A)	2.0 TDI/140 kW 4×4 (A)
Weights				
Kerb weight – incl. driver**	[kg]	1705 {1748}	1740 {1783}	1752 {1795}
Payload – incl. driver**	[kg]	675 {710}	675 {768}	675 {767}
Total weight	[kg]	2305 {2383}	2340 {2460}	2352 {2472}
Max. roof load	[kg]	75		
Max. trailer load w/o brakes	[kg]	750 {-}	750	
Max. trailer load with brakes – 12%	[kg]	2000 {-}	2500 {2000}	
Max. trailer load with brakes – 8%	[kg]	2000 {-}	2500 {2000}	
Max. nose weight	[kg]	100 {-}	100 {80}	
Liquids				
Tank capacity	[l]	60		
Performance/consumption				
Maximum speed	[km/h]	197 {195}	194 {192}	210 {209}
Acceleration 0–100 km/h	[s]	9.7 {9.9}	9.9 {10.1}	8.6 {8.8}
Fuel consumption (1999/100/EC)				
Consumption – urban	[l/100 km]	6.3 {6.4}	6.7	6.6
Consumption – extra-urban	[l/100 km]	4.7 {4.8}	5.1	5.3
Consumption – combined	[l/100 km]	5.3 {5.4}	5.6	5.7
CO ₂ emissions	[g/km]	139 {142}	147	150 {151}
Turning circle diameter	[m]	11.6		

The technical data is valid for the basic version.

** Figures apply to basic version, weight of driver 75 kg.

*** The capacity depends on the position of the backrests and rear seats.

{ } Applies to 7-seater.